November 2021

Net Zero Market Reform

Case for Change and Market Design Options Assessment Framework



nationalgridESO

To help you find the information you need quickly and easily we have published the report as an interactive document.

Page navigation explained



From here you can navigate to any part of the publication

Expand content

Rollover or click the plus symbol to expand or enlarge content

More information

Rollover or click the info symbol for more information

Text Links

Click highlighted orange text to navigate to an external link. Or to jump to another section of the document









Foreword	04
Introduction	05
Project Overview	06
The Case for Change in GB Electricity Markets	07
Introduction	08
The Investment Challenge	09
The Challenge of Managing Energy Imbalances	11
The Location Challenge	13
Summary of Key Challenges and Overlaps	15
Market Design Options	
Assessment Framework	16
Introduction	17
Market Design Elements & Order of Assessment	18
Phase 2 Preliminary Assessment Results	22
Market Design Packages	24
Phase 3 Options	25
Next Steps	26
Appendix	27
Modelling Methodology	27
Market Design Options:	
results breakdown of preliminary assessment	28



Levor D

I am delighted to publish an update on National Grid ESO's Net Zero Market Reform programme of work. Markets are key to ensure safe and reliable electricity supply at an efficient cost to consumers and we know they are going to play a critical role on the road to net zero.



Kayte O'Neill Head of Markets, National Grid ESO Markets need to take us from where we are today to a future energy system that looks very different across supply, demand and networks. The ESO has a privileged role at the heart of the energy system, which means we are uniquely placed to assess how markets need to be reformed over the longer term to achieve net zero.

Our Net Zero Market Reform project is different from other market reform projects we have previously undertaken as we will have a longer-term focus out to 2035 and 2050, and we will look at the full suite of GB electricity markets and policies, not just those run by ESO. The project was established in early 2021, and by April 2022 we aim to share recommendations on the future direction of market reform.

This publication provides an update on the work carried out so far and sets out plans for the remainder of the project. We present our findings of the key challenges identified from our case for change modelling and stakeholder engagement, and our proposed framework for assessing market reform options in the next phase.

Input from our stakeholders through our co-creation workshops, webinars and discussions has been crucial throughout this project so far. As we move into this next phase of more detailed assessment of reforms, it is vital that we continue to work even more closely with our industry partners, as well as with Ofgem and BEIS. I look forward to these discussions over the coming months.

Cti O ntro 0

The Net Zero Market Reform project is exploring how GB electricity markets can support a carbon-free electricity system by 2035, and a net zero economy by 2050, at lowest cost. There is growing industry sentiment that the existing market design requires reform for a future of zero marginal cost generation, volatile supply, and mismatches between where electricity is generated and where it is consumed. The ESO is committed to facilitating net zero operation by 2025. Net Zero Market Reform is a broader workstream considering how electricity markets need to change from 2030 onwards to meet the long-term challenges facing the GB electricity system.

This document sets out our progress to date: it draws together the results of modelling analysis undertaken by external consultants with insights from ESO experts and external stakeholders. We identify the key areas of market design under consideration for reform, our framework for assessing the different design alternatives and the list of options we are taking forward for detailed consideration in our next phase of work. The final output in Spring 2022 will be a set of recommendations on how electricity markets could be reformed.



Project Overview



Ongoing discussions with industry stakeholders and trade associations

90

Project Overview

-

Net Zero Market Reform

Net Zero Market Reform Project Overview 06

The Case for Change in GB Electricity Markets



national**gridESO**

Introduction

During the second phase of our Net Zero Market Reform project, we have developed a more detailed understanding of the medium- to long-term issues facing the electricity system.

Modelling was undertaken on behalf of the ESO by consultants LCP for five snapshot years (2025, 2030, 2035, 2040, 2050) for the three net zero compliant Future Energy Scenarios (FES). The modelling illustrates potential electricity market outcomes if the existing arrangements were to remain in place. It provides a picture of potential future system imbalances and key investment drivers for energy assets, such as wholesale prices, in addition to load factors and capture prices for different generation technologies.

Engagement with internal and external stakeholders focused on the areas of Investment, Flexibility and Location to build a broad picture of current and emerging issues facing asset developers and operators, consumers, suppliers, investors and other market participants.

Taking this analysis together, we have identified three major challenges for markets to address on the road to net zero, as shown on the Venn diagram.

The following section provides further detail on each of these three challenges. There is significant overlap between the three. The interactions and interdependencies between the challenges inform how we frame our assessment of market design reforms.

There is a need to invest at unprecedented scale and pace

There is a need to manage dramatic energy imbalances with flexible and firm technologies across both supply and demand





There is a need to incentivise assets to locate and dispatch where they can

The Investment Challenge

There is a need to invest at unprecedented scale and pace.

Substantial growth in capacity is required across all scenarios to facilitate the electrification of heat, transport and other sectors in line with government targets. Under the Leading the Way FES scenario, total electricity demand is forecast to increase from c.300TWh/ year today to c.700TWh/ year in 2050. The growth in capacity includes emerging flexible technologies and low carbon generation assets, as well as first-of-a-kind (FOAK) generation technologies including bioenergy with carbon capture and storage (BECCS) and hydrogen which will need to be developed to commercial scale.

Increasing volumes of low marginal cost renewable generation are expected to drive a decline in wholesale prices. This will undermine the financial viability of merchant-only and non-supported generation assets. More volatile prices in wholesale, balancing and ancillary service markets create additional investor uncertainty and risk which puts upward pressure on the cost of capital.

What stakeholders said:

At our case for change workshops, stakeholders voted investor uncertainty as the most significant issue in existing market design arrangements. Lack of investment signals for some technologies, an uneven playing field between technologies, and revenue uncertainty were cited as key barriers to achieving the investment needed for net zero.

Substantial volumes of capacity across new and emerging technologies must be built each year

Capacity Build and Retirements: Leading the Way



Most years have over 10GW of new build with the 2030-35 period seeing a sustained build out of 15GW pa. This presents a significant challenge for the market.



Net Zero Market Design must address:



Net Zero Market Reform The Case for Change in GB Electricity Markets 10

The Challenge of Managing Energy Imbalances

There is a need to manage dramatic potential energy imbalances with flexible and firm technologies across both supply and demand.

The future electricity system will be dominated by intermittent renewable generation. Meanwhile, the electrification of heat, transport and other industry will drive a more variable electricity demand profile. The consequent variability in supply and demand will increase the potential for dramatic energy imbalances that will be managed through a combination of firm and flexible capacity.

Markets must incentivise an optimal mix of low carbon generation, firm and flexible (including demand side) capacity. They must minimise the cost of resolving energy imbalances and maintain security of supply in all weather conditions. Markets must also provide short-term signals for flexible actions that mitigate renewables curtailment when balancing supply and demand.

Note that the energy imbalances illustrated in the following section are derived from the FES, which prioritise determining the right mix of generation, demand and flexibility to ensure the ESO can meet its Loss of Load requirements, and do not principally cost-optimise. This means the figures shown may not accurately reflect the absolute volumes of imbalance in the future system but do reflect the broad direction of travel.

An additional consideration is that the FES scenarios do not include projections for longer-term inter-seasonal storage, which may provide further opportunity to manage energy imbalances cost-efficiently.

What stakeholders said:

The value of flexibility needs to be established better at all levels."

Periods of both excess generation and demand will become more extreme and prolonged

Excess Demand/Generation Distribution (GW): Leading the Way



This chart shows the distribution of excess demand/ generation without flexible capacity, assuming that BECCS and nuclear run as baseload*. The proportion of hours with excess generation will increase significantly by 2030 to c.50% of hours. By 2050 this becomes more than 90%. The proportion of excess demand hours becomes less frequent but more extreme.





Net Zero Market Design must address:



Net Zero Market Reform The Case for Change ⊒. **GB** Electricity Markets 12

The Location Challenge

There is a need to incentivise assets to locate and dispatch where they can minimise whole system costs.

To meet net zero, GB faces a three-way trade-off between exploiting the low generation costs of renewables connecting at the network periphery, controlling network reinforcement costs and minimising network congestion costs.

The ESO's current projection of constraint costs (after network reinforcements) to 2040 shows a sharp increase this decade due to renewable generation connecting faster than new transmission capacity can be built. These costs reduce as more transmission infrastructure is built but remain significantly higher than current levels. Efficient locational dispatch signals that account for network congestion close to real time could help to reduce constraint costs.

As more low carbon generation capacity is built, net zero markets must also ensure locational investment signals are both efficient and sufficiently predictable to support assets' investment case.

What stakeholders said:

There are no long-term accurate forecasts for TNUoS. With increasing scale of generation developments, lead times are longer meaning this is becoming an increasing problem. Coupled with the reducing costs of renewables, TNUoS is a much more important cost than it was in the past."

of a new normal of higher constraint cost



ESO projections indicate that congestion costs will rise steeply in the first half of this decade. Costs reduce in the late 2020s, when investments in the transmission network will facilitate the transfer of more renewable generation to southern demand centres.



The Location Challenge

Key Challenges for Location:



Summary of Key Challenges and Overlaps

The market design challenges are summarised below. There are areas of overlaps between the challenges, shown in the table, that must be considered.

There is a need to invest at unprecedented scale and pace There is a need to manage dramatic energy imbalances with **flexible and firm technologies** across both supply and demand





There is a need to incentivise assets to **locate** and **dispatch** in locations that will minimise whole system costs

Net Zero Market Reform Ihe Case ð Change Ξ. **GB** Electricity Markets 5



Market Design Options Assessment Framework



national**gridESO**

Introduction

Meeting the challenges set out in the previous section may require substantial transformation of GB's electricity market design. This chapter firstly describes ESO's assessment criteria for effective net zero electricity markets. Next, we outline the framework for how we currently plan to assess different market design elements. For each of these elements, we then identify the main market design options and set out our preliminary scoring of these options against the criteria. This includes our rationale for excluding a few outlier options for further consideration. The scoping of market design options and initial assessment has been supported by Frontier Economics.

Assessment Criteria

To evaluate potential market reforms, we identified 9 assessment criteria for net zero markets. Specific stakeholder events were held to validate that these objectives are broadly agreed upon by industry.

The criteria listed on the right are not weighted, and the order given does not indicate relative importance.

Assessment Criteria:

Decarbonisation	Provides confidence that carbon targe
Security of Supply	Ensures that adequacy and operability
Value for Money	Ensures that the electricity system (ne run investment) is being delivered efficient
Investor Confidence	Investors are exposed to appropriate r cost of finance is minimised
Deliverability	Transition from current market design appropriate timeframe
Whole System	Facilitates decarbonisation across oth voltages and facilitates demand-side p
Consumer Fairness	The costs of the system are fairly shar
Competition	Facilitates competition within and acro demand and across connection voltage
Adaptability	A market design that can adapt to cha

ets will be met

- y challenges can be met
- etwork build, short run dispatch and long ciently
- risks (e.g. risks they can manage) and the
- to target design is deliverable in an
- er energy vectors, across connection participation
- red across all consumers
- oss technologies, between generation and ges
- anges in technology or circumstances with time frame

Based on the findings in our case for change, we identified 8 key elements of market design and categorised these into 2 broad categories: 'Investment' and 'Operation'.

Due to stronger interactions within the two categories, elements under Investment have been assessed separately from Operation. Within each category we have determined the appropriate sequence in which to assess the elements based on their main dependencies. This sequence is reflected in the order in which the elements are presented in the table below. This includes identifying elements as first and second order priorities. The two broad categories are then assessed in parallel.



The degree to which variable renewables generation is protected

How frequently the market for trading and balancing is settled. Reducing the settlement period may help to reveal the additional

The precise nature and volume of balancing services required are a residual outcome of other market design, such as the proportion of flexibility and intermittent renewables capacity on the system. Changes to ancillary service markets over the longer term should therefore logically follow decisions on other market design elements any designed in conjunction with ongoing ESO work in this area.

We have identified the main alternative options for each market design element. These can loosely be represented on a spectrum of greater central planning of the technology mix, to greater market determination of the technology mix outcome.

Market Design Market Design Options Elements Bespoke arrangements Inter low carbon tech competition Broad investment mechanism Technology-specific support, reflecting different Market-wide regime for any low carbon Single mechanism supporting investment stages of maturity and cost structures of technologies which have become 'cost in low carbon technologies alongside all Low Carbon Central each technology. competitive', and tech-specific support retained other technologies. It could be centralised, Planning where competition is not possible. For example, an equivalent firm power auction with centralised procurement, or decentralised, for example a Supplier Obligation with Wholesale price signals only **Bespoke arrangements Traditional Capacity Market** multiple counterparties. The Broad Investment Mechanism would cover both support for low 2 Technology-specific support, reflecting different Solution could be similar to the current Capacity No capacity-based payments: firm capacity carbon technologies and investment for stages of maturity and cost structures of Market or an alternative means of competitively capacity adequacy. Capacity Adequacy each technology. procuring firm capacity. **Bespoke arrangements** Long term flexibility contracts Joint procurement with firm capacity Short-term market revenue stacking only Technology-specific support, reflecting different A central body procures flexibility requirements Flexibility investments are solely supported A capacity adequacy market is adapted to stages of maturity and cost structures of each under long-term contracts. include flexibility submarkets, for example by by revenue stacking of wholesale revenues flexibility technology. having minimum volumes of firm capacity that from peak prices and arbitrage, Balancing Flexibility could also meet other technical flexibility criteria. service market contracts.

Technology mix centrally planned

Technology mix determined by market 🗲

earns returns from peak wholesale power prices.

Mechanism revenues and short-term ancillary

Operation Market Design Elements

Market Design Elements	Market Design Options						
	National wholesale market (with locational network charges)	Zonal wholesale market	Nodal wholesale				
4 Location	Similar to current arrangements but subject to potential changes to the network charging methodology.	The locational element would be largely removed from network charges, and a small number of wholesale markets (e.g. <6) would be defined.	The formation of a the electrical syste the cost of energy congestion incurre				
	Bilateral s	elf-dispatch	Central dispatch				
5 Dispatch	Generators and buyers contract bilaterally for the sale of electricity, specifying the time of delivery, volume of electricity to be traded and price. Generators decide when to dispatch, and the System Operator manages any imbalances.						

ale market

f a local market clearing price at different nodes in stem. The price calculated at each node reflects gy as well as the cost of energy losses and rred in delivery.

ch and co-optimisation

consumption schedules and the dispatch of demand is determined by the System Operator prated scheduling process. Procurement of onse, reserve and energy is run jointly.



Summary of Market Design Options Under Consideration

The table below summarises the different market design options under consideration for each element:



We assessed the different market design options for each element against our 9 criteria. The criteria have not been given explicit weighting and have been considered independently. The order does not indicate relative importance. The options proposed for each element were given a relative scoring of Positive, Neutral or Negative. These scores are subject to review pending a more detailed assessment in Phase 3.

	Low Cark	oon Central	Planning		Capacity		Capacity Adequ		Capacity Adequacy		Flexibility			Location			Dispatch	
Criteria \ Design Option	Bespoke arrangements	Inter low carbon tech competition	Broad investment mechanism	Bespoke arrangements	Traditional Capacity Market	Broad investment mechanism	Wholesale price signals only	Short term market revenue stacking only	Bespoke arrangements	Long term flexibility contracts	Joint procurement with firm capacity	National Wholesale Market	Zonal Wholesale Market	Nodal Wholesale Market	Bilateral self-dispatch	Central dispatch		
Decarbonisation																		
Security of Supply																		
Value for Money																		
Competition																		
Investor Confidence																		
Consumer Fairness																		
Deliverability																		
Adaptability																		
Whole System																		

This summarises the relative strengths and weaknesses of each reform option. The detailed assessment is provided in the Appendix.

Positive

Neutral I

Negative

No clear differentiation

10

Summary of options taken forward to Phase 3

We have ruled out two options for further consideration in Phase 3 because they did not score highly enough in our preliminary assessment.



Wholesale price signals only

Joint procurement with firm capacity

Due to weaker interactions between the market design elements in the Investment category and those in the Operation category, the options for Investment and Operation have been assessed independently in Phase 2.

Our framework recognises that not all market design options can be practically combined.

'Bespoke arrangements' for low carbon support are currently combined with a traditional Capacity Market; however, as we move to a system domin a broader range of low carbon technologies (including CCS, BECCS etc), the capacity purchased through bespoke low carbon contracts may also p the majority of the firm capacity requirement. Therefore, the case for a separate capacity auction to procure the small remainder of needs is less cle Government is more likely to procure its low carbon contracts taking into account both its green and firm capacity requirements together.

Most low carbon and capacity adequacy options can combine with all flexibility options. The exception is that bespoke arrangements for the procur of capacity adequacy cannot logically be combined with a competitive joint procurement of flexible and firm capacity.

Our framework postulates that the choice of Dispatch option automatically follows the choice of Location option. Based on international precedents, dispatch would be a practical requirement if nodal pricing is adopted and would be most efficiently combined with co-optimisation of energy and re Self-dispatch is therefore treated as incompatible with nodal pricing.

Investment

Operation

24

inated by provide lear.
acity since
urement
ts, central reserve.

Net Zero Market Reform Market Design Options Assessment Framework 24 Eight Investment packages (a-h) and three Operation packages (x-z) will be taken forward into Phase 3 to be assessed. Analysis of the Investment and Operation packages will be done in parallel.



Next Steps

Phase 3 of the Net Zero Market Reform project will assess the first order priority investment and operation design options in depth, considering how different combinations of reforms can work in practice. We will also assess the three second orderpriority elements: low carbon support mechanisms, settlement period duration and future ancillary service market design. Our assessment framework may evolve during the next phase, subject to ongoing consideration of how best to capture the interactions between market design elements.

As with Phase 2, we intend to combine our analytical research with extensive stakeholder engagement. We would be delighted to receive feedback on our work so far and look forward to gathering your input during Phase 3 of this project. We expect Phase 3 to conclude by April 2022 with a set of recommendations on market design and a roadmap for implementation.

You can register for updates on the Net Zero Market Reform project and find our contact details <u>here</u>. To learn more about parallel developments in the ESO Markets team please visit this <u>webpage</u>.



(1)

Modelling Methodology

Developing the Case for Change

Scenario modelling undertaken by LCP 1.

LCP's modelling was based on ESO's three net zero compliant Future Energy Scenarios: Leading the Way, Consumer Transformation and System Transformation.

In the first part of the work, the analysis looked at the fundamental requirements of the future electricity system under each of the scenarios. Modelling five snapshot years (2025, 2030, 2035, 2040, 2050), the analysis identifies the different requirements for flexibility in dealing with a range of weather profiles and extreme events. Key outputs include the required level of firm capacity, the volumes of intraday, monthly and seasonal flex, levels of excess generation, implied load factors for the flexible fleet and system ramping requirements.

The second part of the work focused on projecting electricity market outcomes over the 2025-2050 period if the current market arrangements were to remain in place. The modelling simulates these market outcomes based on assumptions from the three scenarios (including capacity mix). Key outputs from this analysis include projections for each scenario of wholesale price, capture prices of different technologies, and balancing and capacity market outcomes. A further key output is the projected revenue split, for different technologies, between support mechanisms and market revenues (wholesale, balancing, capacity and ancillary) and how this may evolve over time and vary across scenarios.

The market modelling undertaken by LCP was based on a single GB unconstrained merit order and as such does not model redispatch due to locational constraints. The supporting evidence presented in this publication for the case for change on locational signals was derived from internal ESO analysis.

Feedback from external stakeholders 2.

a range of perspectives on current and projected issues with electricity markets. Participants included asset owners, trade associations, energy suppliers and academics.

Energy suppliers
Think tanks/NGOs
Thermal generators
Developers
Government or related bodies
Renewable generators
Trade bodies
Academics
Power exchanges
TOs
Aggregator/flex provider
Storage owners
DNOs
Energy intensive user

lergy intensive use

We ran a series of workshops with internal and external stakeholders to gather



Low Carbon Central Planning

Criteria \ Design Option	Bespoke arrangements	Inter low carbon tech competition	Broad investment mechanism
Decarbonisation	All options satisfy decarbonisation criteria	All options satisfy decarbonisation criteria	All options satisfy decarbonisation criteria
Security of Supply	Security of supply addressed separately	Security of supply addressed separately	Security of supply addressed separately
Value for Money	Lowest WACC and inframarginal rents but highest risk of inefficient technology choices	Lower WACC but higher risk of inefficient technology choices	Higher WACC but lower risk of inefficient technology choices
Competition	Competition limited between technologies	Greater competition between technologies	Full competition between technologies
Investor Confidence	Lower investor risks	More risks with the investor	Greater novelty and more risks with the investor
Consumer Fairness	Not clear this choice affects consumer fairness	Not clear this choice affects consumer fairness	Not clear this choice affects consumer fairness
Deliverability	No significant deliverability challenges	More complex auction arrangements required	Represents material change, so hard to deliver quickly
Adaptability	Long term contracts limit adaptability	Long term contracts limit adaptability	Long term contracts limit adaptability
Whole System	Technology specific support could allow for th This could offer a whole system benefit if the H artificially favouring H2 projects with electricity with optimising across transmission and distril	te targeting of non-electric technologies that may H2 market is otherwise inefficiently small. Howev y support would produce distortions and whole s bution systems.	v suffer from market failures, such as hydroge er, if the H2 market is operating efficiently the ystem disbenefits. There is no clear interactio

Positive

Neutral

Negativ

Capacity Adequacy

Criteria \ Design Option	Bespoke arrangements	Traditional Capacity Market	Broad investment mechanism
Decarbonisation	Not clear	r this choice affects decarbonisation which is dire	ectly addressed by the low carbon investmer
Security of Supply	Target capacity linked to reliability standard	Target capacity linked to reliability standard	Target capacity linked to reliability standar
Value for Money	Lowest WACC and inframarginal rents but higher risk of inefficient technology choices	Lower WACC and inframarginal rents but higher risk of inefficient technology choices	Higher WACC and inframarginal rents but lower risk of inefficient technology choices
Competition	No competition between technologies	Competition between non low carbon technologies	Improved competition for technologies tha can provide green and firm power
Investor Confidence	Low risks with the investor and stable long term price signals secure investment in target projects	Some risks with the investor but stable long term price signals secure investment	Some risks with the investor but stable long term price signals secure investment, though new risks from novel regime
Consumer Fairness		Not clear this choice af	fects consumer fairness
Deliverability	Likely to be able to be adapted from current arrangements	In line with the current system	Represents material change, so hard to deliver quickly
Adaptability	Arrangements can be adapted in response to new developments	Arrangements can be adapted in response to new developments	Arrangements can be adapted in response to new developments
Whole System	Security of electricity supply can support deca for transmission and distribution connected as equal participation of transmission and distribu-	arbonisation of other sectors via electrification. C ssets to participate equally. Likely that all of these ution assets.	urrent Capacity Market arrangements allow arrangements could also accommodate the

Wholesale price signals only

mechanism

Ł	Higher risk of insufficient capacity during some periods
	Higher investor WACC but no inefficient technology choices
t	Competition between all technologies
	Full exposure of investors to market and policy risk
	Gradual change due to current long-term contracts
)	Dynamic response to changes in technology costs
	Security of supply risk may undermine decarbonisation of other sectors via

Positive Neutral Negative No clear differentiation

Flexibility

Criteria \ Design Option	Short term market revenue stacking only	Bespoke arrangements	Long term flexibility contracts
Decarbonisation		Not directly affected, but if less flex	then possibly more RES curtailment
Security of Supply	Firm capacity addressed separately but unclear if there will be sufficient technologies to address ramp rate requirements	Targeted capacity linked to operability and reliability standards	Targeted capacity linked to operability and reliability standards
Value for Money	Higher WACC, but lower risk of over procuring flex	Lower investor WACC but risk of over procurement	Lower investor WACC but risk of over procurement
Competition	Competition likely to favour technologies that primarily provide firm capacity and only some flex	Order of firm capacity and flexibility auctions could create unlevel playing field and tech bias	Joined up procurement of firm capacity and flexibility can provide more of a level playing field
Investor Confidence	Limited bankable revenues associated with flexibility	Some risks with the investor but access to some bankable revenues	Some risks with the investor but access to some bankable revenues. Also greater novelty in approach
Consumer Fairness		Not clear this choice af	fects consumer fairness
Deliverability	Similar to the status quo	Relatively limited change from status quo	More complex auction arrangements required, increasing if in broad investmen mechanism
Adaptability	Dynamic response to changes in technology costs	Arrangements can be adapted in response to new developments e.g. new technologies	Arrangements can be adapted in respons to new developments e.g. new technologi
Whole System	T&D optimisation possible. SofS risks may limit decarbonisation via electrification	T&D optimisation possible but depends on a consistent approach to D flex procurement**	T&D optimisation possible but depends o consistent approach to D flex procurement

* Some of this assessment might change if bespoke arrangements are added alongside to address particular technology issues.

** Assessment assumes that the option does not mandate 100% of required flexibility to be procured long term and leaves some role for shorter term procurement as well.

Joint procurement with firm capacity

Targeted capacity linked to operability and reliability standards

Lower investor WACC but risk of over procurement

Very limited competition between technologies delivering flexibility and limit to demand participation

Low risks with the investor

 Likely to be manageable
Arrangements can be adapted in response to new developments e.g. new technologies
T&D optimisation possible but requires ESO/ DSO coordination

Positive Neutral Negative No clear differentiation

Location

Criteria \ Design Option	National Wholesale Market	Zonal Wholesale Market	Nodal Wholesale Market			
Decarbonisation	Decarbonisation is provided by the low carbon investment mechanism. The locational arrangements considered do not affect the achievability of this. Although they may affect the total cost of achieving decarbonisation, this is captured in the 'low cost' criteria.					
Security of Supply	Unclear	how locational arrangements will affect security	of supply			
Value for Money	Lack of transparent locational signals limits efficient investment	More transparent but less accurate locational signals*	More accurate and transparent but more volatile locational signals			
Competition	National market supports competition	Likely some loss of wholesale competition	Likely greater loss of wholesale competition			
Investor Confidence	More stable but lacking transparency	Potentially greater confidence for location based investments but this could be weakened if there is zonal instability. A novelty premium may also apply	Transparent but sensitive to small local investments. Novelty premium			
Consumer Fairness	Status quo / moderate locational disparity in consumer costs	Reduced average disparity in consumer costs by location but potentially greater disparity by load profile	Likely to increase locational disparities in consumer costs			
Deliverability	Similar to status quo	Significant reorganisation of the wholesale market. Impacts CfDs and transmission rights*	Very significant reform, implies adopting central dispatch which would also complicate other reforms			
Adaptability	Charges can be updated on LRMC timelines	Market price signals automatically adapt to developments	Price signals automatically adapt to developments			
Whole System	Similar to the status quo. May give rise to inconsistent T and D level locational signals	Likely to lead to inconsistency between T level and D level locational signals. (option defined as having no T level sub zonal signals)	Will provide coherent T&D locational signals down to nodal level			

* Experience from some markets in the US has shown that attempts to move to zonal prices can ultimately necessitate a move to nodal prices if there are significant within zone constraints. The current 27 generation zones for network charging suggests this may be a risk given that a zonal wholesale market would realistically only have around half a dozen zones.

Positive Neutral

Negative No clear differentiation

Dispatch

Criteria \ Design Option	Bilateral self-dispatch	Central dispatch and co-optimisat				
Decarbonisation	In principle, equally capable of supporting decarbonisation					
Security of Supply	In principle, equally capable of beir	g consistent with security of supply				
Value for Money	Slightly less efficient wholesale price signals price signals for flexibility and reserve assuming that the ESO is a better forecaster than the market at the relevant time resolution and the central optimisation algorithm is reasonable.	Slightly improved price signal because con assuming ESO better forecaster than mark optimisation algorithm is reasonable.				
Competition	Full bilateral traded markets provide good conditions for competition, provided that there is sufficient liquidity in the markets.	Historically in GB, central dispatch has bee power. However, central dispatch is applied sufficient plurality of market participants th				
Investor Confidence	Current bilateral trading arrangements provide investor confidence regarding wholesale markets. However, short term wholesale price signals reflect market participant expectations of ESO reserve requirements, rather than ESO's expectation. If the ESO is a better forecaster of reserve requirements in the relevant timeframe then bilateral trading will provide less transparent wholesale price signals for flexibility and reserve because more of the signal will go through the BM.	Likely to be some novelty premia in the GB approach from other jurisdictions. Short ter reserve requirements. If this is more accura more transparent wholesale price signals for				
Consumer Fairness	As today	No clear change relative to status quo				
Deliverability	This is the status quo	Central dispatch would have major delivera possible reforms				
Adaptability	Potentially more adaptable because contracting is less constrained	Potentially less adaptable as it relies more materially constrain he ability to adapt to re				
Whole System	No clear interactions. Both self dispatch and central dispatch could support the decarbor To optimise under central dispatch the ESO will need to be aware o	nisation of other energy vectors and the optim f distribution constraints to optimi <u>se but this s</u>				

tion

astraint costs are reflected in the wholesale price at the relevant time resolution and the central

n more susceptible to the exercise of market I in many jurisdictions in the world and with is issue should be able to be controlled.

context but investors will be familiar with this rm price signals will reflect ESO's expectations of ate in the relevant timeframe then this will provide or flexibility and reserve.

ability challenges and could complicate other

on central processes but this is unlikely to elevant changes

isation across transmission and distribution. should not be a barrier.

Positive

Neutral Negative

Ancillary Services

Services procured by the ESO to support operation of the electricity system.

Baseload Generation

An electricity generator that tends to operate at constant output for 24 hours a day throughout the year.

Bioenergy with Carbon Capture and Storage (BECCS)

The coupling of bioenergy with carbon capture and storage to capture the CO2 produced during combustion. This process delivers negative emissions.

Capacity

The power output of an electricity generation technology usually measured in Watts (or kW, MW or GW).

Capacity Market

The Capacity Market is designed to ensure security of electricity supply. This is achieved by providing a payment for reliable sources of capacity, alongside their electricity revenues, ensuring they deliver energy when needed.

Contract for Difference

A contract between the Low Carbon Contracts Company (LCCC) and a low carbon electricity generator, designed to reduce its exposure to volatile wholesale prices.

Curtailment (Grid Curtailment)

This is when the output from a generation unit connected to the electricity system is reduced due to operational balancing.

Demand Side Flexibility

The ability of energy users to adjust demand in response to market signals.

Electrolysis

Electrolysis is the process of using electricity to split water into hydrogen and oxygen.

Excess Demand

For the LCP analysis, this is defined as electricity demand net of generation from intermittent renewables, baseload low carbon generation (nuclear and BECCS) and assumed interconnector flows.

Excess Generation

For the LCP analysis, this is defined as electricity generation from intermittent renewables, baseload low carbon generation (nuclear and BECCS) and assumed interconnector flows, net of electricity demand.

Flexibility

The ability to adjust either the supply or demand of electricity.

First of a Kind (FOAK)

Refers to the first item or generation of items to use a new technology or design, when the cost tends to be substantially higher than later generations.

Types of generation that can only produce electricity when their primary energy source is available. For example, wind turbines can only generate when the wind is blowing.

Load Factor

Load factors are a measure of how active a generation plant or technology type is across a year, expressed as a percentage. It is calculated by dividing the total electricity output across the year by the maximum possible generation.

Interconnectors

Transmission assets that connect the GB market to markets in other countries and allow market participants to trade electricity between these markets.

Intermittent Generation

Loss of Load Expectation (LOLE)

Used to describe electricity security of supply. It is an approach based on probability and is measured in hours/year. It measures the risk, across the whole of winter, of demand exceeding supply under normal operation. This does not mean there will be loss of supply for 3 hours per year. It gives an indication of the amount of time, across the whole winter, which the Electricity System Operator (ESO) will need to call on balancing tools such as voltage reduction, maximum generation or emergency assistance from interconnectors. In most cases, loss of load would be managed without significant impact on end consumers.

Net Zero

When the total amount of greenhouse gases emitted in a year reaches zero, after all emissions and all carbon sequestration has been accounted for. This is the current UK target for 2050.

Peak Demand, Electricity

The maximum electricity demand in any one fiscal year. Peak demand typically occurs at around 5:30pm on a weekday between November and February. Different definitions of peak demand are used for different purposes. FES uses the Average Cold Spell (ACS) definition which is consistent with the treatment of demand in the electricity Capacity Market.

Time of Use Tariff

A charging system that is established in order to incentivise consumers to alter their consumption behaviour, usually away from high electricity demand times.

Weighted Average Cost of Capital (WACC)

The weighted average of the cost of equity and the cost of debt, where the weighting is provided by the gearing ratio.

Net Zero Market Reform / Glossary 34





national**gridESO**