

Master Artwork

NGTS 3.2.4

Issue 1

September 92



The Electrical Standards for SHE Transmission's area are non-maintained versions of National Grid Technical Specifications that are applicable to the SHE Transmission System only. These specific versions are not subject to National Grid change control and all queries about their applicability and content should be directed to SHE Transmission in the first instance. (Should Users require the change controlled versions of the GB Transmission System National Grid Technical Specifications please see the National Grid Extranet or Livelink system where applicable).



National Grid
Technical
Specification

NGTS 3.2.4
Issue 1
September 1992

**Current Transformers
for Protection and
General Use on the
132 kV, 275 kV and
400 kV Systems**

CONTENTS	Page
Foreword	1
Scope	1
References	1
General Requirements	1
Performance Requirements	3
Testing Requirements	3
Approval Procedure	4
Schedules	5
Appendix	19

Authorised for Issue by:

A handwritten signature in black ink, appearing to read "M B Humphries".

M B Humphries
General Manager
Technology and Science Division

© National Grid Company plc 1992

**No part of this publication may be reproduced,
stored in a retrieval system, or transmitted in
any form or by any means electronic, mechanical,
photocopying, recording or otherwise, without
the written permission of the NGC obtained from
the issuing location.**

**Registered Office
National Grid House
Kirby Corner Road
Coventry
CV4 8JY**

**Registered In
England and Wales
No. 2366977**

Published by:

**The National Grid Company plc
Burymead House
Portsmouth Road
Guildford, Surrey GU2 5BN**

CURRENT TRANSFORMERS FOR PROTECTION AND GENERAL USE ON THE 132 kV, 275 kV AND 400 kV SYSTEMS

FOREWORD

This Specification defines the functional requirements for current transformers for protection and general use of maximum primary voltage rating 145, 300 and 420 kV for use on the National Grid Company (NGC) Transmission System. It supports the more general conditions defined in the companion documents NGTS 1 and NGTS 2.2.

1 SCOPE

This a Functional Specification for current transformers.

Functional requirements for settlement metering current transformers are separately specified in NGTS 3.2.6.

2 REFERENCES

This Specification makes reference to or must be read in conjunction with:

IEC 185	Current Transformers
IEC 694	Specification for Common Requirements for High Voltage Switchgear and Controlgear Standards
BS 3938	Specification for Current Transformers
NGTS 1	Overview, National Grid System
NGTS 2.1	Substations
NGTS 2.2	Switchgear for the National Grid System
NGTS 2.3	Transformers and Reactors for use on 132, 275 and 400 kV Systems
NGTS 2.6	Protection
NGTS 3.2.6	Current and Voltage Measurement Transformers for Settlement Metering of the 33 kV, 66 kV, 132 kV, 275 kV and 400 kV Systems

3 GENERAL REQUIREMENTS

In addition to the requirements of NGTS 1 and NGTS 2.2 the following clauses apply:

3.1 All Current Transformers

3.1.1 Current transformers shall be designed for a minimum service life of 40 years as detailed in NGTS 2.2 clause 3.1.1.

3.1.2 Current transformers shall be in accordance with IEC 185 (BS 3938).

3.1.3 Secondary ratings and transformation ratios shall be selected from the attached Schedules and shall be specified in the contract.

3.1.4 Current transformer cores shall be arranged in accordance with NGTS 2.1 Appendix B and the positioning of current transformers in the substation shall be in accordance with NGTS 2.1 Appendix C.

3.1.5 Secondary terminals and connections shall be suitable for their required purpose.

3.1.6 Secondary connections shall be identified in accordance with IEC 185 (BS 3938).

3.1.7 The rated continuous primary current of the current transformer shall be chosen to exceed the maximum continuous rating of the associated circuit and shall be selected from the standard values detailed in IEC 185 clause 4.

3.1.8 A thermal short-time current rating (I_{th}) shall be assigned to all current transformers in accordance with clause 8 of IEC 185. The value of I_{th} shall not be less than the corresponding value for the associated switchgear or transformer primary equipment.

3.1.9 For maintenance purposes, current transformer secondary wiring shall be provided with short-circuiting facilities remote from the current transformer.

3.2 Additional Requirements for Post-Type Current Transformers

3.2.1 External porcelain insulation and insulation co-ordination shall meet the requirements of NGTS 2.2.

3.2.2 An insulation test tap shall be provided for the purpose of performing capacitance and dielectric loss ($\tan \delta$) measurements of the primary insulation during routine maintenance. The test tap terminals shall be suitably identified.

3.2.3 A single secondary terminal box shall be mounted on the transformer to accommodate the necessary secondary terminal connections.

3.3 Additional Requirements for GIS Current Transformers

3.3.1 Current transformers shall be mounted internally or externally to the GIS enclosure. Adequate protection shall be provided for externally mounted current transformers.

3.3.2 The enclosures of externally mounted current transformers shall be in accordance with NGTS 2.1 clause 4.3.1.

3.4 Additional Requirements for Ring-Type Current Transformers for Oil Immersion (Transformer Application)

3.4.1 Current transformers mounted internally to transformers shall be capable of operating in an environment as detailed in NGTS 2.3.

3.4.2 Current transformers supplied as loose equipment for transformer application shall be equipped with secondary terminals or shall be supplied with leads of suitable length, capable of satisfying the test requirement of clause 5.1 (vii) of this Specification.

3.5 Additional Requirements for Measurement/Protection and Class P Protective Current Transformers

3.5.1 Measurement/protection and class P protective current transformers with a rated primary current of 2500 A or below and with untapped secondary windings shall have a rated secondary current of 1A (as selected from IEC 185 clause 5). The rated secondary current for current transformers of this primary rating with tapped secondary windings shall be 1 A corresponding to the highest transformation ratio.

3.5.2 Measurement/protection and class P protective current transformers with a rated primary current in excess of 2500 A shall have a rated secondary current selected from the values stated in IEC 185 clause 5.

4 PERFORMANCE REQUIREMENTS

4.1 General

All current transformers shall comply with the requirements of IEC 185 (BS 3938) for the primary ratings detailed in NGTS 1 and NGTS 2.2, and also with the following:

4.2 Protection Type A Current Transformers

Protection type A current transformers shall meet the performance requirements of Class X (BS 3938) and shall provide accurate transformation up to the maximum fault current rating of the associated main plant. This performance shall be maintained under both transient and steady-state conditions without saturation. Type A current transformers shall also meet the performance requirements of Schedule 9 of this Specification.

4.3 Protection Type B Current Transformers

Protection type B current transformers shall meet the performance requirements of Class X (BS 3938) and shall provide accurate steady-state transformation up to the maximum fault current rating of the associated main plant. Type B current transformers shall also meet the performance requirements of Schedule 9 of this Specification.

4.4 Dual Purpose Measurement/Protection Current Transformers

Current transformers intended for the dual purpose of measurement and protection shall meet the performance requirements of BS 3938 clause 4.1.1 and Schedule 9 of this Specification.

4.5 Interposing Current Transformers

Where a short duration overload capability is assigned to the main current transformers then the associated interposing current transformers shall be capable of carrying the corresponding current.

4.6 Line Drop Compensation Current Transformers

Line drop compensation current transformers shall comply with accuracy class 5 of IEC 185.

5 TESTING REQUIREMENTS

5.1 Type Tests

All current transformers shall be tested in accordance with IEC 185 (BS 3938). The following tests shall also be performed:

- (i) Temperature Rise - The thermal time constant of all equipment shall be determined on both rising and falling temperature.
- (ii) Radio Interference - RIV tests in accordance with IEC 694.
- (iii) Accuracy at Short-Term Continuous Current Levels - Current transformers which have a measurement specification shall have their errors determined at a current of 12000 A for 420 kV rating and 7500 A for 300 kV rating respectively.
- (iv) Leakage Test on Oil System - For current transformers using an oil insulation system, the supplier shall demonstrate leak-free performance of the transformer.
- (v) Leakage Test on Gas System - For current transformers using a gas insulation system, the supplier shall demonstrate compliance with NGTS 2.2 clause 4.7.3.

(vi) Ring-type current transformers for transformer application shall be tested to simulate their immersion in transformer oil. The supplier shall propose a representative test for the agreement of NGC.

(vii) Current transformer leads as detailed in clause 3.4.2 of this Specification shall withstand a power frequency test voltage of 10 kV (peak).

Routine tests shall be performed before and after all type tests. No significant changes between these results is permitted.

5.2 Routine Tests

All current transformers shall be tested in accordance with IEC 185 (BS 3938). The following tests are also required:

- (i) Capacitance / dielectric loss ($\tan \delta$) measurements over the voltage range 10 kV to rated voltage.
- (ii) Measurement of the primary and secondary winding resistances.

6 APPROVAL PROCEDURE

Requirements for the approval of current transformers are as detailed in NGTS 2.2. Where required, Appendix A of this Specification shall be completed by the supplier in support of approval.

LIST OF SCHEDULES

- 1 Overhead Line Feeder Circuits
- 2 Synchronous Compensators Associated with Auto-Transformers
- 3 Static Compensators (Reactors and Capacitors) Associated with Auto-Transformers
- 4 Series Reactors
- 5 Shunt Reactors
- 6 Bus Sections and Couplers
- 7 Auto-Transformer Circuits
- 8 Transformer Neutral and Neutral End Current Transformer Units for use with Supergrid Auto-Transformers and Shunt Reactors
- 9 Table of Particulars for 420 kV, 300 kV and 145 kV Current Transformers

SCHEDULE 1 - OVERHEAD LINE FEEDER CIRCUITS

System Voltage kV	Rated Current of Switchgear A	Class X Protection Current Transformers		Measurement/Protection Current Transformers		
		Rated Continuous Thermal Current A	Turns Ratio	Extended Primary Current Rating %	Thermal	Accuracy
Main	Busbar					
275	2000	2000	1/600/1200	1/600/1200	170	420
275	2500	2500	1/600/1200	1/600/1200	210	420
400	4000	4000	1/1000/2000	1/2000	200	500
						<u>2000/1000/1</u>

SCHEDULE 2 - SYNCHRONOUS COMPENSATORS ASSOCIATED WITH AUTO-TRANSFORMERS

Compensator Rating	Voltage kV	Current A	Rated Current of Switchgear A	Class X Protection Current Transformers			Measurement/Protection Current Transformers						
				Rated Continuous Thermal Current	Turns Ratio	Main REF*	UEF**	Connections	Extended Primary Current Rating %	Thermal Accuracy	Back Up Accuracy	Rated Transformer Ratio	Reverse Power
60	13	2665	3000	3000	1/600	1/600	1/300	1/600	-	-	-	3000/5	3000/5

* REF - restricted earth fault

** UEF - unrestricted earth fault

SCHEDULE 3 - STATIC COMPENSATORS (REACTORS AND CAPACITORS) ASSOCIATED WITH AUTO-TRANSFORMERS

Compensator Rating	Voltage	Current	Rated Current of Switch-gear	Class X Protection Current Transformers		Measurement/Protection Current Transformers		Rated Transformation Ratio
				Rated Continuous Thermal Current	Turns Ratio	Extended Primary Current Rating %	Thermal Accuracy	
MVA	kV	A	A	HV Connections	Compensator Protection	REF*	UEF** and Instantaneous Earth Fault	
60	13	2665	3000	1/600	1/600	1/1500 #	-	3000/5
30+30	13	1335 + 1335	2000	1/600	1/1500	1/300 +	-	3000/5

* REF - restricted earth fault

** UEF - unrestricted earth fault

A relay may be required

+ 300/1 ratio to be specified when earth fault current is restricted to 300 A by NER.
1500/1 ratio to be specified when earth fault current is restricted by impedance of earthing transformer only.

SCHEDULE 4 - SERIES REACTORS

Rating MVA	System Voltage kV	Current A	Rated Current of Switchgear A	Class X Protection Current Transformers		Measurement/Protection Current Transformers		
				Rated Continuous Thermal Current A	Turns Ratio	Extended Primary Current Rating %		Rated Transformation Ratio
						Main	Busbar	
90	132	395	800	800	1/500/1000	1/500/1000	-	<u>1200/600/1</u>
750	275	1575	2000	2000	1/600/1200	1/600/1200	170	170
750	275	1575	2500	2500	1/600/1200	1/600/1200	210	<u>1200/600/1</u>
1320	400	1905	4000	4000	1/1000/2000	1/2000	200	<u>2000/1000/1</u>
2000	400	2890	4000	4000	1/1000/2000	1/2000	200	<u>2000/1000/1</u>

SCHEDULE 5 - SHUNT REACTORS

Rating MVA	System Voltage kV	Current A	Rated Current of Switchgear A	Class X Protection Current Transformers				Measurement/Protection Current Transformers			
				Rated Continuous Thermal Current A		Turns Ratio		Extended Primary Current Rating Thermal and Accuracy %		Rated Transformation Ratio	
				Located near Switchgear	Located in Bushing	Main Protection	Feeder Protection or if Applicable	Connections Protection if Applicable	Located near Switchgear	Located in Bushing	
100	275	210	2000	2000	500	1/600/1200	1/600/1200	1/600/1200	170	-	
100	275	210	2500	2500	500	1/600/1200	1/600/1200	1/600/1200	210	-	
200	400	290	4000	4000	500	1/1000/2000	1/1000/2000	1/2000	200	-	
										2000/1000/1 *	

* 0.5 A relay to be specified.

SCHEDULE 6 - BUS SECTIONS AND BUS COUPLERS

System Voltage kV	Rated Current of Switchgear A	Class X Protection Current Transformers		Measurement/Protection Current Transformers	
		Rated Continuous Thermal Current A	Turns Ratio Busbar	Extended Primary Current Rating %	Rated Transformation Ratio
275	2000	2000	1/600/1200	170	420
275	2500	2500	1/600/1200	210	420
400	4000	4000	1/1000/2000	200	500

SCHEDULE 7 - AUTO TRANSFORMER CIRCUITS

Nominal Rating MVA	System Voltage kV	Current A	Rated Current of Switchgear A	Class X Protection Current Transformers		Measurement/Protection Current Transformer				Extended Primary Current Rating %	Rated Transformation Ratio	
				Turns Ratio		Extended Primary Current Rating %						
				Main	Located near Swigear	HV and LV Connections	Busbar	Back Up LV	Thermal *	Accuracy **		
120	275	250	2500	2500	450	1/600/1200	1/600/1200	1/600/1200	210	-	1200/600/1	
	132	530	800	800	800	1/600/1200	1/500/1000	1/500/1000	-	-	1200/600/1	
180	275	350	2500	2500	660	1/600/1200	1/600/1200	1/600/1200	210	-	1200/600/1	
	132	790	1250	1250	1250	1/600/1200	1/500/1000	1/500/1000	110	-	1200/600/1	
240	275	500	2500	2500	970	1/600/1200	1/600/1200	1/600/1200	210	-	1200/600/1	
	132	1050	2000	2000	1600	1/600/1200	1/500/1000	1/500/1000	170	135	1200/600/1	
240	400	350	4000	4000	610	1/600/1200	1/1000/2000	1/2000	200	-	2000/1000/1	
	132	1050	2000	2000	1600	1/600/1200	1/500/1000	1/500/1000	170	135	1200/600/1	

* Designed to cater for 150% overload

** Designed to cater for 200% overload

At busbar stations where post-type CT housings are installed and LV connection protection is specified, the back-up protection is to be supplied from the Type A 1/600/1200 CT.

SCHEDULE 7 - AUTO TRANSFORMER CIRCUITS (Cont'd)

Nominal Rating MVA	System Voltage kV	Current A	Rated Current of Switchgear A	Class X Protection Current Transformer		Measurement/Protection Current Transformer				Rated Transformation Ratio
				Rated Continuous Thermal Current A*		Turns Ratio		Extended Primary Current Rating %		
				Main	Located near Bushing	HV and LV Connections	Buster	Back Up LV	Thermal *	Accuracy **
500	400	720	4000	4000	1100	1/600/1200	1/1000/2000	1/600/1200	200 210	200 210 <u>180</u> <u>1200/600/1</u>
	275	1050	2500	2500	1600	1/600/1200	1/600/1200	1/600/1200	200 210	200 210 <u>110</u> <u>1200/600/1</u>
750	400	1080	4000	4000	1700	1/600/1200	1/1000/2000	1/600/1200	200 210	200 210 <u>270</u> <u>1200/600/1</u>
	275	1580	2500	2500	2500	1/600/1200	1/600/1200	1/600/1200	200 210	200 210 <u>150</u> <u>1200/600/1</u>
1000	400	1440	4000	4000	2200	1/600/1200	1/1000/2000	1/600/1200	200 210	200 210 <u>350</u> <u>1200/600/1</u>
	275	2100	2500	2500	3200	1/600/1200	1/600/1200	1/600/1200		

* Designed to cater for 150% overload.

** Designed to cater for 200% overload.

SCHEDULE 8 - TRANSFORMER NEUTRAL AND NEUTRAL END CURRENT TRANSFORMER UNITS FOR USE WITH SUPERGRID AUTO TRANSFORMERS AND SHUNT REACTORS

TABLE A - NEUTRAL CURRENT TRANSFORMERS

275/132 kV, 400/275 kV and 400/132 kV auto-transformers and 400 kV and 275 kV Shunt Reactors (11 kV primary insulation)			
Type	Primary Conductor Rating for 3 secs (A)	Turns Ratio	Function
Transformer 275/132 kV (Up to 360 MVA)	8200	1/600/1200	At Least 2 Secondaries, Neutral Earth Fault Check, Fault recorder etc
Transformer 400/275 kV (Up to 1000 MVA)	6600	1/1000/2000	"
Transformer 400/132 kV (Up to 360 MVA)	10 600	1/1000/2000	"
Shunt Reactor 275 kV (Up to 100 MVA)	2100	1/600/1200	Neutral Earth Fault Check
Shunt Reactor 400 kV (Up to 200 MVA)	2900	1/1000/2000	"

SCHEDULE 8 (Cont'd)

TABLE B - NEUTRAL END CURRENT TRANSFORMERS (3 SINGLE PHASE WINDINGS STARRED)

275/132 kV, 400/275 kV and 400/132 kV auto-transformers and 400 kV and 275 kV Shunt Reactors (11 kV Primary Insulation)			
Type	Primary Conductor CMR ($I_{hv} - I_h$) amp	Turns ratio	Function
Transformer 275/132 kV (Up to 360 MVA)	820	1/600/1200	Auto Transformer Overall Protection
Transformer 400/275 kV (Up to 1000 MVA)	660	1/600/1200	"
Transformer 400/132 kV (Up to 360 MVA)	1060	1/600/1200	"
Shunt Reactor 275 kV (Up to 100 MVA)	210	1/600/1200	Shunt Reactor Overall Protection
Shunt Reactor 400 kV (Up to 200 MVA)	290	1/1000	"

SCHEDULE 9 - TABLE OF PARTICULARS FOR 420 kV, 300 kV AND 145 kV CURRENT TRANSFORMERS

Reference Clauses	CT Designation	Ratio		Knee-Point Voltage (V_k) or IEC Rating and Class	Magnetising Current (mA)	Max Sec Res (ohms)
		Turns	Current			
4.2 to 4.4	420 kV, 4000 A					
		(i) Prot A	1/1000/ <u>2000</u>	300 ($R_{ct} + 7.5$)		
		(ii) Prot B	1/2000	60 ($R_{ct} + 5$)	40 at $\frac{V_k}{2}$	5.0 at 75°C
		(iii) Prot B Special Ratio	1/600/ <u>1200</u>	82 ($R_{ct} + 3$)	60 at $\frac{V_k}{2}$	2.4 at 75°C
		(iv) Measurement/Protection	1/1000/2000	30 VA Class 1 5P20		
			2000/1	30 VA Class 1 5P10		
			1000/1			
4.2 to 4.4	300 kV, 2000 or 2500 A					
		(i) Prot A	1/600/ <u>1200</u>	160 ($R_{ct} + 7.5$)		
		(ii) Prot B	1/600/ <u>1200</u>	82 ($R_{ct} + 3$)	60 at $\frac{V_k}{2}$	2.4 at 75°C
		(iii) Measurement/Protection	1/600/1200	30 VA Class 1 5P20		
			1200/1	30 VA Class 1 5P10		
			600/1			

Note: For tapped current transformers the knee-point voltage, magnetising current and secondary resistance are specified for the full winding, shown underlined.

SCHEDULE 9 (Cont'd)

Reference Clauses	CT Designation	Ratio		Knee-Point Voltage (V_k) or IEC Rating and Class	Magnetising Current (mA)	Max Sec Res (ohms)
		Turns	Current			
4.2 to 4.4	145 kV, 2000A					
	(i) Prot A	1/600/ <u>1200</u> 1/500/ <u>1000</u>		50 ($R_{ct} + 17$) 60 ($R_{ct} + 12$)	60 at $\frac{V_k}{2}$	2.4 at 75°C
	(ii) Prot B	1/500/ <u>1000</u>		95 ($R_{ct} + 2.5$)		
	(iii) Measurement/Protection	1/600/1200	1200/1	30VA Class 1 5P20		
			600/1	30VA Class 1 5P10		

Note: For tapped current transformers the knee-point voltage, magnetising current and secondary resistance are specified for the full winding, shown underlined.

NGTS 3.2.4
Page 18 issue 1
September 1982

APPENDIX A

INFORMATION TO BE SUPPLIED BY THE TENDERER

A1 GENERAL DETAILS


1	Manufacturer	
2	Type reference Drawing reference (s)	
3	Production commencement	
4	Type test report number (s)	
5	Test specification (s)	
6	Category and date of approval	

A2 GENERAL TECHNICAL DATA

1	Rated voltage	kV	
	Maximum operating voltage	kV	
2	Rated primary current	A	
3	Rated short-time current, thermal (1 second)	kA	
	Rated short-time current, dynamic (peak)	kA	
4	Capacitance / dielectric loss	pF	
5	Power frequency withstand voltage (dry/wet)	kV	
	Lightning impulse withstand voltage (dry)	kV	
	Switching impulse withstand voltage (dry/wet)	kV	
6	Admissible static load (primary terminals)	kN	
	Admissible dynamic load (primary terminals)	kN	
	Cantilever test load (primary terminals)	kN	
	Declared porcelain breaking strength	kNm	
7	Insulation test tapping (Yes/No)		
8	Porcelain insulator creepage distance	mm	
	Porcelain insulator arcing distance	mm	
9	Primary insulation:		
	(a) Insulating medium		
	(b) Quantity	m ³	
	(c) Type of insulating oil (if applicable)		
	(d) Gas insulation (if applicable)		
	(i) Maximum operating pressure	MPa	
	(ii) Minimum operating pressure	MPa	
	(iii) Normal operating pressure	MPa	
	(iv) Leakage rate	torr l/ s	
	(v) Maximum permissible dew point temperature	°C	
10	Total Weight	kg	

A3 TRANSFORMER SECONDARY DETAILS

Winding Number	1	2	3	4	5
Ratio					
Secondary current (A)					
Rated burden (VA)					
Measurement class					
Protection class					
Extended current rating (A)					



Date 04 June 1996

Our Ref

Your Ref



Mr J S B Cooper
The National Grid Company plc
Burymead House
Portsmouth Road
Guildford
Surrey
GU2 5BN

The National Grid Company plc Burymead House
Technology and Science Division Portsmouth Road
Business Management Branch Guildford
Personnel and Administration Surrey
Tel 01483 569951 GU2 5BN
Fax 01483 507373
Direct Dialling
01483 507484

ENGINEERING DOCUMENT DESPATCH

Please find enclosed the following document(s) for insertion into your NGTS 2.2 ring-binder:

NGTS 3.2.9 Issue 1
Post Insulators for Substations

Number of copies: 10

Please confirm receipt of the above document(s) by either returning a photocopy of this letter to the above address, or via E-mail to JSC at BURYMEAD.

A handwritten signature in black ink, appearing to read "PP D Cooper".

JONATHAN COOPER
Administration Services



Technology and
Science Division

Registered Office:
National Grid House
Kirby Corner Road
Coventry CV4 8JY

Registered in
England and Wales
No 2366977

NTS 3-2-9 Issue #1

● Copy to:

C Ferguson
I Kinner
J Laxard
R Harcke
QA - CARLINE
TSD Business Mgr.
TSD Car Mgr.
TSD TXL Mgr.

Sent on 11/6/96.

32/11274	1	A	32/11274	132kV Static - Capacitor Maintenance Vehicle Store General arrangement and details **
32/10908	1	O	32/10908	275kV substation static capacitors switch hpusse details Sheet 4
32/10907	1	A	32/10907	13kV switch house general details - sheet 2 **
32/10906	1	A	32/10906	13kV switch-house sheet 1 details - General. **
32/10905	1	C	32/10905	13kV switch-house general arrangement **
32/10904	1	A	32/10904	Reactive compensator compound - Plant building **
32/10227	1	3	X2578120	Current transformer assembly in High voltage housing. **
32/10226	1	1	X2430616	Current transformer housing. **
32/10216	1	O	07065/2	Detail of builders work showing pockets required. **
32/10215	1	O	07065/1	Proposed arrangement of pipework and equipment and details of builders work. **
DNO	SHT	REV	ORIG_NO	TITLE
32/8830	1	2	A2399051	Compressor room foundation plan. **
32/8809	1	O	D2/4393/5	Partitions at first floor
32/8807	1	O	DP85	Lighting heating and power for oil plant building. **
32/8773	1	O	G/M228/2	Details of Timber frames
32/8772	1	O	G/M228/1	Warm air ductwork details
32/8771	1	O	D2/4393/3	Substation control building
32/8770	1	O	D2/4393/2	Substation control building
32/8733	1	A	32/8733	132kV substation elevations of oil plant building. **
32/8732	1	B	32/8732	132kV substation details of oil plant building. **
32/8731	1	A	32/8731	275kV substation elevations of plant building. **
32/8730	1	C	32/8730	275kV substation - Details of plant building. **
32/8572	1	O	SK1792	Foundation location Rolls Royce C6NFL brush SOA 7-25 alternator. **
32/7849	1	3	E5440315	OPR and tank foundations. **
32/7507	1	O	8/782/2/A	Detail layout of computer room floor panels. first floor **
DNO	SHT	REV	ORIG_NO	TITLE
32/7506	1	O	8/782/2/B	Layout of computer floor panels **
32/7505	1	O	8/782/2/C	Building details **
32/6934	1	G	32/6934	275/132kV substation control building sections **
32/6753	1	O	32/6753	Details of prefabricated light building mark II **
32/6733	1	O	32/6733	275/132kV substation control building modification to control room floor **
32/6719	1	O	32/6719	Isometric view of rationalised control building **
32/6717	1	O	32/6717	Metering master clock mounting details **
32/6699	1	O	32/6699	Foundation details and location of site hut **
32/6695	1	K	32/6695	275/132kV substation control building ground floor plan and foundation details **
32/6679	1	J	32/6679	275/132kV substation control building - First floor plan and roof plan **
32/6616	1	G	32/6616	275/132kV substation control building plans and elevations **
DNO	SHT	REV	ORIG_NO	TITLE
32/5123	1	O	32/5123	Relay building additional access to relay room **
32/5072	1	A	32/5072	Relay building extension - Elevations **
32/4631	1	A	32/4631	Relay building extension **
32/3811	1	A	32/3811	Relay building additional trenchwork **
32/3216	1	O	32/3216	275kV substation - Details of modifications to existing relay building **
32/3194	1	C	32/3194	275kV substation oil plant building - Plan and sections **
32/3193	1	A	32/3193	275kV substation oil plant - Building elevations **
32/3192	1	A	32/3192	275kV substation oil plant building - Building details **
32/2674	1	A	32/2674	Relay building elevations. **
32/2670	1	A	32/2670	Relay building, Details of windows and door surrounds. **
32/2669	1	A	32/2669	Relay building details. **
32/2668	1	A	32/2668	Relay building sections. **
DNO	SHT	REV	ORIG_NO	TITLE
32/2667	1	A	32/2667	relay building plan showing clerestory lighting. **
32/2666	1	B	32/2666	Relay building general plan. **
32/2367	1	O	66.1/2.239	Details of 11kV switch house
32/151	1	J	33.1/134.24	Arrangement of building to accomodate auxiliary equipment, stores, offices and etc **
32/127	1	O	32/127	Single circuit tower type S2. **
31/67106	1	B	A806	GENERAL ARRANGEMENT SURGE ARRESTER STRUCTURE Norton s/s
31/67105	1	A	AA03/T1/L1	GENERAL ARRANGEMENT OF ACCESS LADDER Norton s/s
31/67104	1	A	AA03/T1	GENERAL ARRANGEMENT SINGLE BAY GANTRY TOWER T1 Norton s/s
31/67103	1	A	AA3/G1	GENERAL ARRANGEMENT CROSS GANTRY G1 FOR SINGLE SPAN GANTRY AA03
31/67102	1	A	AA01/T2/SC1	GENERAL ARRANGEMENT OF INTER BAY SCREEN FOT TOWER T2 STRUCTURE AA01 Norton s/s
31/17310	1	A	633Z1KA60328	General Assembly support structure MKIV & V CVT
31/16847	1	A	F201484	Frame Assembling T155 Point D ##
DNO	SHT	REV	ORIG_NO	TITLE
31/16846	1	A	F200980	Charpente T155 Components of Frame ##
31/16845	1	B	F201467	Frame Assembling T155. Slipering Support Support Tripolaire Glissant (Fluoduc Superpose) ##

THE NATIONAL GRID COMPANY PLC

NATIONAL GRID TECHNICAL SPECIFICATIONS

TRANSMISSION PLANT SPECIFICATION (APPLICATION)

FINAL APPROVAL

792

GROUP

Switchgear & Power Electronics

TITLE

Post Insulators for Substation

NUMBER

NGTS 3.2.9 Issue 1 May '96

GUIDANCE NOTE ON FINAL APPROVAL

The issue of a new document or an amendment must have the prior approval of the Group Manager and the authorisation of the General Manager Technology and Science Division.

ACTION	NAME	SIGNATURE	DATE
1. Final Check *	<u>John McGrath</u> (Author)	<u>JMC</u>	<u>2/5/96.</u>
2. Approval	<u>Ian Welch</u> (Group Manager)	<u>I. Welch</u> With Refs P1+5	<u>8/5/96</u>
3. Authorisation	<u>Mike Humphries</u> (General Manager) Technology & Science Division	<u>M.B.Humphries</u> - subject to marked up changes	<u>MMR</u>
4. Final Check Print Issue Index		<u>Catherine Ferrier</u> <u>D. Ferrier</u>	<u>4-6-96</u>

* Please advise of any special distribution requirements

approval.gm



Date 10 June 1999

Our Ref

Your Ref Master Library

Mrs Carol Mortimer
The National Grid Company plc
Kelvin Avenue
Leatherhead
Surrey
KT22 7ST

The National Grid Company plc
Engineering and Technology
Research Programme and Facilities
Business Resources

Kelvin Avenue
Leatherhead
Surrey
KT22 7ST
Tel 01372 383838
Fax 01372 383722
Direct Dialling
01372 383720

ENGINEERING DOCUMENT DESPATCH

Please find enclosed the following document for insertion into your NGTS 3.2.4 ring-binder:

NGTS 3.2.4 Issue 3, May 99
Current Transformers for Protection and General Use on the 132 kV, 275 kV and 400kV Systems

Number of copies: 10

Please confirm receipt of the above document(s) by either returning a photocopy of this letter to the above address, or via E-mail to CZM at LEATHERHEAD.

Note that, with reference to page 11 of the QA Manual, document holders are responsible for the destruction or suitable marking and archiving (eg "Superseded") of withdrawn or obsolete documents.

P.P. S. Mortimer

JO HARRINGTON
Business Resources



Registered Office:
National Grid House
Kirby Corner Road
Coventry CV4 8JY

Registered in
England and Wales
No 2366977

DOCUMENT DISTRIBUTIONS

Tick when completed


Document No: NGTS 3.2.4 Issue No: 3 Date: May 99

Prior to Copying

- ❖ NGTS/TAL/QSP/DMI Update the Index page to go to copying with document
- ❖ Issue 1 documents enter on to Quality Team under Document Manager
- ❖ Make up distribution list
 - Add names on the master distribution
 - Add names subscribers list
 - Add any names added by the author
 - If Issue 2 of any document call up previous issue and change issue level and date. Check all people on above **embolden** items are added.
 - If Document is an NGTS/TAL Issue 1, level 3, call up relevant level 2 document and copy distribution list then check all people on above **embolden** items are added.
- ❖ Print a Printing and Distribution list in 'Letters and Labels' for amount of copies required.
- ❖ Complete a copying form and send with document only to Sean keeping hold of printing and distribution list and approval sheet.

When document comes back from copying

- ❖ Print letters and labels using guide overleaf
- ❖ Stamp documents with appropriate stamp plus external companies have an disclaimer.
- ❖ Stamp two document station documents with document station stamp
- ❖ Send out document
- ❖ Issue to all holders on Quality Team check Issue no., date and issue date are correct
- ❖ F10 Document Station copy of document to be filed straight away
- ❖ F10 Document Station letter to be filed in Catherine F's p&d box file in her cupboard
- ❖ Library Document station document goes to Carol to be filed in the Library
- Library Document station Letter, Print & Dist. List and Approval Sheet - staple together and either put in EDICT box (if document sent to outside companies) or file in the appropriate Printing and Distribution Folder.
- ❖ If receipt required for document, put Carol's Master Library letter in the receipts box marked up that it is a receipt for Master Library and Both Admin Doc Stations
- ❖ Stock Copies - for issue 1 make up hanging pocket for cupboard and file. If Issue 2 etc. replace existing stock copies with new ones.
- ❖ Mark in the diary that the document has been issued and the date
- ❖ Tick off the deadline in the diary at the front of the binder
- ❖ Put a chasing note in red in the appropriate column in diary, four weeks after date of issue for documents that need receipts
- ❖ Ensure a print master is filed
- ❖ Put Master Artwork in an envelope with outside marked up with Document No., Issue No and Date to be filed in the archives
- ❖ Retrieve previous issue & previous distribution list and approval form for microfilming



Printing and Distribution Form

Document Number: NGTS 3.2.4

Issue Level: 1, Sep 92

Number of copies: 69

Date into printing 1.6.99 Date Issued Date entered into EDICT

Holder Code:	Name:	Company:	Copies
Mr S Needham	Mr S Needham	The National Grid Company plc	1
Datem Solutions -	Miss Sarah Hemsley	The National Grid Company plc	1
Alstom T & D Systems Ltd	Mr A P Gee	Alstom T & D Systems Ltd	1
LHD Library	Mrs C A Mortimer	LHD Library Doc Stain	Copy No 5
Master Library	Mrs Carol Mortimer	The National Grid Company plc	10
Mr C Ferguson	Mr C Ferguson	The National Grid Company plc	Copy No 12
Mr I Funnell	Mr I Funnell	The National Grid Company plc	Copy No 25
Mr J Lapworth	Mr J Lapworth	The National Grid Company plc	Copy No 21
Mr K White, Eng Dev	Mr K White	The National Grid Company plc	5
Mr B Swindle	Mr B Swindle	The National Grid Company plc	2
Northern Ireland Electricity	Mr A Sinnott	Northern Ireland Electricity	1
PM North Document Unit	Miss S Darby	The National Grid Company plc	11 and 1 UC
North East Area	Mr D S Summers	The National Grid Company plc	1
North West Area	Attn Kathryn Benn	The National Grid Company plc	3
Mr D Legg	Mr D Legg	The National Grid Company plc	1
LHD NCT Document Station	Mr P Garbett	The National Grid Company plc	Copy No 3
Scottish Power plc	Mrs D Ference	Scottish Power plc	1
Siemens plc	Mr R Townsend	Siemens plc	1

Holder Code:	Name:	Company:	Copies
Instrument Transformers Ltd	Mr P Munro	Instrument Transformers Ltd	1
ABB Power T&D Ltd	Mr B T Connelly	ABB power T&D LTD	1
AMEC Power Ltd	Mr R M Rees	AMEC Power Ltd	1
Ms B Ennism	Ms B Ennism	The National Grid Company plc	1
ABB Power T&D Limited	Mr N Noble	ABB Power T&D Ltd	1
ET OHL & Eng Performance Manag	Mr A Heath	Wokingham Document Station	Copy No 51
GEC T&D Transmission Switchgr	Mr A R Penfold	GEC T&D Transmission Switchgear Ltd	1
Yorkshire Electricity	Mrs M Brennan	Yorkshire Electricity	1
Mr A L Bennett	Mr A L Bennett	The National Grid Company plc	1
Mr D Poulton	Attn Miss K Shearer	The National Grid Company plc	1
Mr W Pirie	Mr W Pirie	The National Grid Company plc	1
South West Area	Dr I C Davis	The National Grid Company plc	1
Hams Hall Library	Mrs T Jobling	The National Grid Company plc	1
Mr B Pendrich	Mr B Pendrich	The National Grid Company	1
Mr A Marratt	Mr A Marratt	The National Grid Company plc	1
ET Substations & Cables Mangr.	Mr R Houlgate	The National Grid Company plc	Copy No 8
Mr R Houlgate	c/o Mr P Jamman	The National Grid Company plc	Copy No 14
Mr J McGrath	Mr J McGrath	The National Grid Company plc	Copy No 50
British Short Circuit Testing	Mr P Anderson	British Short Circuit Testing	1
RPF Library	Mrs J Collis	The National Grid Company plc	Copy No 2
South East Area	Mr D Christie	The National Grid Company plc	1
LHD Room F10 Document Station	Mrs J G Harrington	LHD Room F10 Document Station	Copy No 9

Holder Code:	Name:	Company:	Copies
Mr T Fawcett	Mr T Fawcett	The National Grid Company plc	1
Mr W J Wilkinson	Mr W J Wilkinson	The National Grid Company plc	1

THE NATIONAL GRID COMPANY plc

NATIONAL GRID TECHNICAL SPECIFICATIONS
TRANSMISSION PLANT SPECIFICATION (APPLICATION)

FINAL APPROVAL

GROUP SUBSTATIONS + CABLES

TITLE CURRENT TRANSFORMERS FOR PROTECTION &
GENERAL USE

NUMBER NGTS 3.2.4

ISSUE 3

GUIDANCE NOTE ON FINAL APPROVAL

The issue of a new document or an amendment must have the prior approval of the Group Manager and the authorisation of the General Manager Engineering and Technology.

ACTION	NAME	SIGNATURE	DATE
1. Final Check of document and distribution list *	<u>J. H. Houghton</u> (Author)	<u>14/5/1999</u>	
2. Approval	<u>R. G. Houghton</u> (Group Manager)	<u>R. G. Houghton</u>	<u>14/5/99</u>
3. Authorisation	<u>JEP</u> (General Manager) Engineering & Technology	<u>JEP</u>	<u>21/8/99</u>
4. Final Check Print Issue			

* Please advise of any specific distribution requirements

Engineering Document Master Distribution List

This list is current as of 10/12/98

Surname	Company	Comments
AUTHOR		1 copy - except for NC authors who only receive the letter (0 copies)
Mr A Heath	Wokingham Document Station The National Grid Company plc	1 copy of all engineering documents
ET OHL & Eng Performance Man		
Mr I M Welch	The National Grid Company plc	1 copy of all Substations and Cables related engineering documents
ET Substations & Cables Mangr.		
Mrs T Jobling	The National Grid Company plc	1 copy of all engineering documents
Hans Hall Library	Network Services Planning Kelvin Avenue	
Mrs C A Mortimer	LHD Library Doc Statn	1 copy of all engineering documents
LHD Library		
Mr P Garbett	The National Grid Company plc	1 copy of all engineering documents and NCT TR(E)s. If other group, 0 TR(E)s "letter for info"
LHD NCT Document Station	The National Grid Company plc Kelvin Avenue	
Mrs J Harrington	LHD Room F10 Document Station	1 copy of all engineering documents
LHD Room F10 Document Station	The National Grid Company plc	
Mrs Carol Mortimer	The National Grid Company plc	6 copies of all documents for stock
Master Library	Kelvin Avenue	
Miss M Woolstenholmes	The National Grid Company plc	1 copy - TALS, 1 copy - TGNE34, 1 copy of index of NGTSS
Miss M Woolstenholmes	National Grid House	
Mr A L Bennett	The National Grid Company plc	1 copy of all engineering documents
Mr A L Bennett	Kirby Corner Road	
Mr A Marnatt	The National Grid Company plc	1 copy of all SCTs, NGTSS, TGNS, Index of Engineering Documents
Mr A Marnatt	Saltend Site Office	
Mr B Pendrich	The National Grid Company	1 copy of all NGTS documents
Mr B Pendrich	Caravelle Court	
Mr D Legg	The National Grid Company plc	1 copy of all engineering documents
Mr D Legg	National Stores	
Attn Miss K Shearer	The National Grid Company plc	1 copy of all engineering documents
Mr D Poult	Sceptre House	
Mr H Kinch	The National Grid Company plc	1 copy of TDCs only
Mr H Kinch	Littlebrook	
Mr J A Downes	The National Grid Company plc	1 copy of NGTS 2.6, 2.7, 2.9, 2.12, 2.13, 2.15, 2.19 & level 3s, plus 1 copy of LSIs, QSPs
Mr J A Downes	Kelvin Avenue	

Surname	Company	Comments
Mr J McGrath	The National Grid Company plc Hockstone Park	1 Copy of all engineering documents - But No SCTs, TPSSs or TALS
Mr J McGrath		
Mr K White	The National Grid Company plc Great Park Road	5 copies of all engineering documents
Mr K White, Eng Dev		
Mr L Hall	The National Grid Company plc Kelvin Avenue	1 copy of all TDCs
Mr L Hall		
Mr N Jacks	The National Grid Company plc St Catherine's Lodge	1 copy - NGTS, TGN, TDC, TPSS and Index of Eng docs
Mr N Jacks		
Mr R Houlgate	The National Grid Company plc Kelvin Avenue	1 copy of all Substation & Cables related Docs and NGTS & TAL 2.2, 2.5, 2.17 and level 3s
Mr R Houlgate		
Mr R J A Smith	The National Grid Company plc St Catherine's Lodge	TDC 6000 series
Mr R J A Smith		
Mr R Shand	The National Grid Company plc St. Catherine's Lodge	1 copy of all SCTs
Mr R Shand		
Mr S Boswell	The National Grid Company plc Kirklington Road	1 copy of all TDCs
Mr S Boswell		
Mr S Needham	The National Grid Company plc St Catherine's Lodge	1 copy of all engineering documents - instead of Les Chalke
Mr S Needham		
Mr T Fawcett	The National Grid Company plc NSIG	1 copy: NGTS, SCT, TAL, TDM, TDC, TGN, TPSS
Mr T Fawcett		
Mr T J Taylor	The National Grid Company plc St Catherine's Lodge	1 copy of all TDCs
Mr T Taylor		
Mr W J Wilkinson	The National Grid Company plc Kirklington Road	1 copy of all engineering documents
Mr W J Wilkinson		
Mr W Pirie	The National Grid Company plc Drakelow Substation	1 copy of NGTSS, TGNS, SCTs, TDC, TDMs and TRs
Mr W Pirie		
Ms B Enniss	The National Grid Company plc Kirby Corner Road	1 copy of NGTSS, TGNS and TAL 2.15
Ms B Enniss		
Mr D S Summers	The National Grid Company plc North East Area	1 copy all engineering documents
Mr D S Summers		
Altn Kathryn Benn	The National Grid Company plc North West Area	3 copy all engineering documents except 7 copies of TDCs
Altn Kathryn Benn		
Mrs J Rudman	The National Grid Company plc 1st floor, Brookmead PM Document Unit - Brookmead	3 Controlled copies of all engineering documents and 1 Uncontrolled Copy 1 controlled copy of TRE's
Mrs J Rudman		

Surname	Company	Comments
Miss S Darby PM North Document Unit	The National Grid Company plc Hootstone Park	8 copies of all docs except, 7 copies - TPMPs, 4 copies -SCTs and TDCs
Mrs J Collis RPF Library	The National Grid Company plc Kelvin Avenue	1 copy of NGTSS, TALS, LSIs, DMIs + TPSs
Mrs C Donoghue Scottish Hydro-Electric plc	Scottish Hydro-Electric plc South Inch Business Centre	1 copy of non-confidential SCTs, TPSs, TGNS, TPMPs, TRs, TDCs, Index of Eng Docs - Subscription Expires 30 May 1999 plus NGTSS 2.6+ level 3s 2.10 & 2.22 Subscription Expires 29 September 1999, LM1 - 9 A4
Mr S Bruen. Scottish Power plc	Scottish Power plc Power Systems Business Head Offi	1 Copy of non-confidential SCTs, TPSs, TGNS, TPMPs, TALS, TRs, TDCs, LMs, Index of Eng Docs. - Subscription Expires 31 March 1999 plus NGTSS Subscription Expires 29 November 1998
Mr D Christie South East Area	The National Grid Company plc London Road	1 copy of all engineering documents